## INDUSTRIAL VACUUM CLEANERS

Oilvac 60 - Ultra compact vacuum cleaner for oil & chips - OIL AND CHIPS





- ✓ Oil and chips recovery single phase industrial vacuum system for mechanical workshops.
- ✓ Exraction and recovery of liquids, oil and emulsions mixed with chips, dust and sludge.
- ✓ Large steel sieve basket for separation and collection of chips, and special fine filters for deep filtration of fine dust and metallic particles.







- ✓ Liquids capacity up to 60lt
- ✓ Integrated float for maximum suction stop reached

Voltage	V - Hz	230 - 50
Power	kW	1,1
Max waterlift	mmH2O	2400
Max air flow	m³/h	180
Suction inlet	mm	40
FILTER UNIT		
Filter Type		Bag
Surface - Diameter	cm²-mm	2.000 - 400
Media - Filtration		Polypropilene - 100 micron
Air load on filter	m³/m²/h	900
Collection tank		Steel
Discharge system		Tilting container
Capacity	lt.	65
Liquids capacity	lt.	55
Solids capacity	lt.	10
Floating device		N./A.
Level detector for automatic motor cut off		Yes
VOLUME		

Dimensions

cm

53 x 68 x 89h

All data mentioned in this document may change without notice. Tutti i dati riportati in questo documento potrebbero variare senza preavviso.





## SUCTION UNIT

Suction is developed by one carbon brushes by-pass motor which is activated byan independant switch placed on a solid, metallic head. Special noise buffers reduce noise level to work safety standards.



## **FILTER UNIT**

A float system stops the suction process once the liquid in the containment tank reaches maximum level, so avoiding possible leakage. A bag filter protects the motor from solid elements and residues.



The vacuum unit is mounted on a robust metal structure, fitted with resistant industrial wheels ideal for mobile service on uneven surfaces.

The container is compact and contains a sieve grid which separates solid particles from liquid.

Tutti i dati riportati in questo documento potrebbero variare senza preavviso.