

## INDUSTRIAL VACUUM CLEANERS

### SKY 500 - Oil Mist Collectors - OIL AND CHIPS



METALWORKING



OEM ORIGINAL  
EQUIPMENT MANUFACTURERS



#### SUCTION UNIT

Voltage	V - Hz	400 - 50
Power	kW	0,18
Max air flow	m <sup>3</sup> /h	250
Suction inlet	mm	100
Noise level (EN ISO 3744)	dB(A)	62



#### FILTER UNIT

Filter Type		Multilayer
Surface - Diameter	cm <sup>2</sup> -mm	2300 - 280



#### VOLUME

Dimensions	cm	39x47h
Weight	kg	18

- ✓ Compact, powerful and light.
- ✓ Reduced electrical consumption
- ✓ Easy and fast maintenance.
- ✓ Easy mount on the machine.
- ✓ Quick and easy filter replacement system.

All data mentioned in this document may change without notice.  
Tutti i dati riportati in questo documento potrebbero variare senza preavviso.



## SUCTION UNIT

The suction unit is a low power turbine with high air flow.



## FILTER UNIT

Filtration versatility: multilayer filter (standard) or pleated high-surface filter cartridge with coalescent pre-filter



## COLLECTION UNIT

The extracted and filtered oils and emulsions are thickened on the wall of the vacuum cleaner allowing recovery by drainage pipe.



## OPTIONALS

- ✓ Painted metal kit for Air outlet fan
- ✓ Installation kit with riser.
- ✓ Installation kit with adjustable riser.
- ✓ Wall mounting kit.
- ✓ Column stand adjustable from 1.5 to 2.5 meters for fixing to the floor.
- ✓ Kit Cyclon Pre-filter