

INDUSTRIAL VACUUM CLEANERS

W 3 - Single phase industrial vacuum cleaner - INDUSTRIAL SINGLE PHASE



CHEMICAL-PHARMACEUTICAL



CLEANING CONTRACTORS



TEXTILE



PLASTICS



✓ 100% steel construction.

✓ Suitable for wet and dry service, also simultaneously.

✓ Detachable container with direct bagging option.

✓ Filter with wide filtration surface for fine dusts, with integrated manual cleaning system.



SUCTION UNIT

Voltage	V - Hz	230
Power	kW	3 x 1,1
Max waterlift	mmH ₂ O	2400
Max air flow	m ³ /h	540
Suction inlet	mm	80



FILTER UNIT

Filter Type		Star
Surface - Diameter	cm ² -mm	20.000
Cleaning system		Manual



COLLECTION UNIT

Collection tank		Steel
Discharge system		Roll-out container
Capacity	lt.	65 / 100



VOLUME

Dimensions	cm	58 x 60 x 135h
------------	----	----------------



All data mentioned in this document may change without notice.
Tutti i dati riportati in questo documento potrebbero variare senza preavviso.



SUCTION UNIT

Suction is developed by three carbon brushes by-pass motors which are activated by independant switches placed on a solid, metallic head. Special noise buffers reduce noise level to work safety standards.



FILTER UNIT

A polyester pocket filter inside the steel filter chamber protects the suction system. A filter shaking lever allows easy cleaning for longer lasting filter life.



COLLECTION UNIT

The steel container has an easily deattachable container for quick disposal of suctioned material.



OPTIONALS

- ✓ Nomex heat resistant filter up to 250°
- ✓ Absolute Hepa filter H14
- ✓ Class M filter
- ✓ Class M teflon hydro-oleophobic filter
- ✓ Antistatic class M filter
- ✓ Stainless steel collection tank
- ✓ Stainless steel collection tank and filter chamber
- ✓ Earth grounding
- ✓ Sieve grid with discharge valve and level detector
- ✓ Longopac 20m bag container
- ✓ Cyclon for filter protection