




DATI TECNICI AUTOCENTRANTI TECHNICAL DATA

AUTOCENTRANTI GUIDA SEMPLICE SINGLE GUIDE CHUCKS

Dimensioni	Coppia consentita al pignone Nm	N° giri ghisa RPM	N° giri acciaio RPM	Forza serraggio kgm	Precisione ghisa	Precisione acciaio	Portata con supporto kg
160/180	120	3600	4600	3100	0,03	0,02	150
200/230	160	3000	4000	3700	0,04	0,025	250
250/270	180	2500	3500	4600	0,04	0,025	500
315	200	2000	2800	5500	0,05	0,03	1000
400	280	1600	2000	6500	0,06	0,04	2500
500	360	1000	1300	7200	0,1	0,05	4000
630	460	800	1000	8000	0,1	0,06	6000
800	500	600	-	8500	0,15	-	8000
1000/1250	600	400	-	9000	0,18	-	11000



POSSIBILITÀ DI SERRAGGIO TIGHTENING RANGE

GRIFFE MONOBLOCCO

Ø mm	D1	D2	D3	D4	D5	Ø mm	D1	D2	D3	D4	D5
80	2-27	22-46	45-69	25-50	48-71	80	-	-	-	-	-
100	3-33	25-56	56-87	32-62	62-93	100	-	-	-	-	-
125	3-50	34-74	72-115	39-83	80-125	125	3-50	34-76	75-118	52-96	95-125
160	3-64	42-100	94-154	50-107	98-160	160	3-64	42-97	88-146	62-121	115-160
200	4-90	52-135	120-202	60-145	130-200	200	4-90	50-130	105-190	72-156	133-200
250	5-118	62-174	145-256	77-188	160-250	250	5-118	58-165	125-235	86-197	160-250
315	10-131	78-200	172-299	90-215	190-315	315	10-131	65-182	145-265	103-226	190-315
400	10-180	85-252	210-380	103-272	230-400	400	10-180	72-228	165-329	127-294	230-400
500	20-235	120-335	245-476	140-357	276-500	500	20-235	120-410	200-485	110-400	190-500
630	30-335	160-465	352-630	180-487	345-630	630	30-335	140-590	210-665	120-570	200-630
800	150-482	282-614	448-780	302-634	468-800	800	150-482	252-736	328-812	240-724	316-800
1000	-	-	-	-	-	1000	100-600	350-1080	430-1150	425-1070	500-1150
1250	-	-	-	-	-	1250	250-800	450-1200	550-1300	500-1250	650-1300

GRIFFE BASE + BLOCCHETTO TENERO

PASSAGGIO BARRA MAX. Ø REALIZZABILE

Ø Mandrino	Foro standard	Max realizzabile
80	16	18
100	20	23
125	32	34
160	42	46
200	55	65
250	76	86
315	103	110
400	136	144
500	190	205
630	250	280
800	320	320
1000	460	460
1250	560	560